


Technical Specifications

HP Z24f G3 FHD Display




Front

1. Power button

Technical Specifications

HP Z24f G3 FHD Display



Back

1. OSD control	7. DisplayPort™ connector (out)
2. Security cable slot	8. USB Type-B port (upstream)
3. Master power switch	9. USB port
4. Power connector	10. USB port (Battery charging 1.2, 7.5W)
5. HDMI port	11. USB port
6. DisplayPort™ connector	12. USB port (Battery charging 1.2, 7.5W)

Technical Specifications

Panel Specifications	Display Size (Diagonal)	23.8"
	Panel Technology	IPS
	Refresh Rate	60 Hz
	Panel Bit Depth	8 bit (6bit + FRC)
	Aspect Ratio	16:9
	Brightness (Typical)	300 nits
	Contrast Ratio (Static)	1000:1
	Dynamic Contrast Ratio	10M:1
	Flicker Free	Yes
	Pixel Pitch	0.2745mm
	Pixels Per Inch (Ppi)	93 PPI
	Backlight Lamp Life Minimum (To Half Brightness - In Hours)	40 k
	Backlight Type	Edge-lit
	Screen Treatment	Anti-glare
	Hardness	3H
	Haze	25%
	Response Time (Typical)	5ms GtG (with overdrive)
	Horizontal Viewing Angle (Typical Cr>10)	178°
	Vertical Viewing Angle (Typical Cr>10)	178°
	Panel Active Area (W X H)	527.04(H)*296.46(V)
NOTE: Performance Specifications Represent The Typical Specifications Provided By HP's Component Manufacturers; Actual Performance May Vary Either Higher Or Lower.		
Color Management	Factory Color Calibrated	Yes (Delta E <=2)
	Calibrated Color Presets	sRGB, BT.709, P3 D65 (Production after Feb '21)
	RGB Channel Adjust	Yes, Gain
	Default Color Temperature	sRGB
Color	sRGB	99 %
	P3 D65	85%
Monitor Specifications	Bezel	4-sided Micro Edge
	Color	(Head) Turbo Silver; (Stand) Turbo Silver
	Tilt	-5 to +20°
	Swivel	±45°
	Pivot	±90
	Height Adjust Range	150mm
	VESA Mounting	100 mm x 100 mm (bracket included)
	Security Lock Ready	Standard Security Lock Slot
	Detachable Stand	Yes
	Warranty (Number of Years)	3/3/0 for LA, NA, EMEA, APJ; (3/3/3 in select APJ Countries)
	Low Blue Light Mode	Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)
	Display Management Software	HP Display Center
	On Screen Display	Joystick
	On Screen Controls	Brightness +, Color, Image, Input, Power, Menu, Management, Information, Exit
User-Assignable Function Buttons	Native Resolution	Yes, 4 buttons
	Native Resolution Footnote	Full HD (1920 x 1080)
	Maximum Resolution	1920×1080 @ 60HZ

Technical Specifications

Preset Graphic Modes/Supported Resolutions	640 × 480@60Hz 800 × 600@60Hz 1024 × 768@60Hz 1280 × 720@60Hz 1280 × 800@60Hz 1280 × 1024@60Hz 1440 × 900@60Hz 1600 × 900@60Hz 1680 × 1050@60Hz 1920 × 1080@60Hz
High Definition Video Formats	720 × 480p@60Hz 720 × 576p@50Hz 1280 × 720p@50Hz 1280 × 720p@60Hz 1920 × 1080p@50Hz 1920 × 1080p@60Hz
Minimum Vertical Scan Rate	50 Hz
Maximum Vertical Scan Rate	60 Hz
Minimum Horizontal Scan Rate	30.0 kHz
Maximum Horizontal Scan Rate	75.0 kHz
Maximum Pixel Clock	170 MHz
Languages	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)
Connector Types	DisplayPort™ DisplayPort™ Out HDMI USB-A USB-B (Hub enablement)
	1 DisplayPort™ 1.2 1 DisplayPort™ 1.2-out 1 HDMI 1.4 4 USB-A 3.2 Gen1 (2 for battery charging 1.2, 7.5W) 1 USB-B
Special Features	DaisyChain/DisplayPort Multi stream Transport (MST)
Power & Operating Specs	Power Supply Power Source Power Consumption- MAX Energy Saving/Stand By Mode Power Consumption- Typical Power Cable Length
	Internal 100 – 240 VAC 50/60 Hz 58 W 0.5 W 26 W 1.9m
ENERGY STAR Data	Operational Mode at 100 VAC Operational Mode at 115 VAC Operational Mode at 230 VAC
	11.06 W 11.1 W 11.1 W
EU Energy Efficiency Class (ERP Lot-5)	On-mode Power Consumption Annual Power Consumption Energy Efficiency Class
	12.5 W 19 kWh D
Operating Conditions	Operating Temperature - Celsius Operating Temperature - Fahrenheit Non-Operatin Temperature - Celsius Non-Operating Temperature - Fahrenheit Operating Humidity Non-Operating Humidity
	5° – 35°C 41° – 95°F –34° – 60°C 29° – 140°F 20 – 80% Relative Humidity (non-condensing) 5 – 95%

Technical Specifications

Environmental Features and Certifications	Operating Altitude	0 – 5,000 m (16,400 ft.)	
	Non-operating Altitude	0 – 12.192 m (40,000 ft.)	
Mercury-free LED display backlighting	Yes, Mercury-free LED backlighting		
Arsenic-Free Display Glass	Yes		
Low Halogen	Yes		
	WW application		
	CE,CB,KC/KCC/NOM/PSB/EAC/GS/TUV-S/ISO 9241-307/		
	Low Blue Light/ BIS/cTUVus/CCC/SEPA/Energy		
	Star/TCO/TCO Certified Edge/VCCI/FCC/BSMI/Vietnam		
	MEPS/Australian-New Zealand		
	MEPS/WEEE/UAE/Ukraine/ERP/ISC		
Agency Approvals And Certifications			
Microsoft WHQL Certification	Win 11		
ENERGY STAR® Certified	Yes		
EPEAT® Registered	Yes		
Regions need to verify by country	CEL Grade 1*		
	*Monitors produced before June 1st 2024 comply with China regulation GB 21520-2015.		
China Energy Label			
TCO Certified Edge	Yes		
TCO Certified	Yes		
SmartWay Transport Partnership - NA only	Yes (NA sku)		
Contains Recycled Plastics	Contains Recycled Plastics	80.76%	
	Recyclable Packaging (Box, packing materials)	100% recyclable packaging.	
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H)	53.84 x 19.5x 48.93 cm	21.2x7.68 x 19.26 in
	Product Dimensions (Packed) (W x D x H)	62.5 x 37.3 x 14.2 cm	24.61 x 14.69 x 5.59 in
	Display Head Dimensions (Unpacked without stand) (W x D x H)	53.84 x3.85x 31.37 cm	21.2x 1.52 x 12.35 in
	Base Area Footprint (w x d mm)	232 X 195 mm	9.13 X 7.7 in
	Bezel Measurements - Metric	Bottom Cover:530.2mm	Bottom Cover:20.87in
	Product Weight (Unpacked with stand)	4.7 kg	10.4 lb
	Product Weight (Packed)	7.2 kg	15.6 lb
	Product Weight (Head Only)	3.5 kg	7.7 lb
What's in the box?	Documentation kit DP1.4 Cable (1.8m) HDMI 1.4 cable (1.8m, Production after May'21) USB 3.0 Type A to B (1.8m) Power cable VESA Adapter Cable Holder		
User Guide and Warranty Languages	User Guide Languages	English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian	

Technical Specifications

Warranty Languages

Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.

Technical Specifications

Copyright © 2024 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries.

ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

Summary

Change Log

Change Log			
January 12, 2021	V1 to V2	Updated	Technical Specifications
February 28, 2021	V2 to V3	Updated	Energy Efficiency Class
April 15, 2021	V3 to V4	Update	VESA Mounting Specs
June 1, 2021	V4 to V5	Update	Color Management
June 24, 2021	V5 to V6	Update	What's in the box? Section
March 22, 2023	V6 to V7	Update	VESA Mounting specs
December 21, 2023	V7 to V8	Added	Windows 11
May 17, 2024	V8 to V9	Remove	CEL and CECP
May 30, 2024	V9 to V10	Added	CEL and disclaimer