

Station d'Accueil USB-C 4K, Station d'Accueil pour Triple Moniteur UHD 4K, Mac et Windows, USB C vers HDMI et DisplayPort, 60W Power Delivery, Hub 5x USB 5Gbps

N° de produit: DK30CH2DPPD



This TAA compliant 4K USB-C™ dock for Mac and Windows® laptops takes productivity to a whole new level, with support for triple 4K monitors - a first in the market. The USB Type-C dock provides 60W charging power, and 5x USB 3.0 ports to connect your peripheral devices. It's the perfect accessory for your Dell™ XPS 15, Chromebook Pixel™, or another USB-C enabled PC laptop.

The dock also connects to USB 3.0 laptops with a USB-A port (using a USB-C to A cable such as the USB315AC1M, sold separately).

Note: Power Delivery to charge your laptop is not available through USB-A, and only dual display is supported.

The 4K USB-C Dock for Mac and Windows lets you create a three-monitor Ultra HD workstation. Connect:

2x 4K DisplayPort (DisplayLink) at 4096 x 2160 resolution / 3840 x 2160 @ 60Hz and

1x 4K HDMI (DP Alt Mode) at 4096 x 2160 resolution @ 24Hz / 3840 x 2160 @ 30Hz

For high-resolution applications, the universal laptop docking station can also connect to a 5K display (5120 x 2880 resolution) at 60Hz, by connecting the two DisplayPort ports to a single 5K display.

This triple-monitor docking station lets you connect your peripherals to transform your laptop into a full-sized workstation. With five USB 3.0 ports (1x USB Type-C and 4x USB Type-A incl 1x Fast-Charge port), a Gigabit Ethernet port, headset jack and separate 3.5 mm audio and microphone ports, you have all the connections you need for maximum performance.

Using a single cable, the USB-C docking station with Power Delivery (up to 60W) will power and charge your laptop, and power your peripherals with its 120W power adapter.

The DK30CH2DPPD is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Certifications, rapports et compatibilité



Applications

- Ideal for 4K video editing or working with high-resolution graphics
- Work on multiple documents simultaneously in office applications
- View multiple monitors at a glance, in financial or investment firms
- Ideal for surveillance and monitoring

Spécifications techniques

- **DOCK COMPLET** : Dock USB-C avec 3 sorties vidéo (2xDP & 1xHDMI), 60W Power Delivery, 4x USB-A & 1x USB-C 5Gbps Hub, Gigabit Ethernet, casque + ports audio séparés haut-parleur/micro, K-Slot & câble USB-C de 1m; Inclut l'utilitaire de mise à jour DisplayLink
- **TRIPLE AFFICHAGE SUR MACBOOK AIR** : Activez trois moniteurs étendus sur un MacBook Air / Pro (Apple M1/M2/M3) qui ne supporte pas nativement plus d'un écran externe; Connectivité vidéo flexible simple, double ou triple avec les ports DisplayPort ou HDMI
- **FONCTIONNE AVEC N'IMPORTE QUEL PC** : Simplifiez votre déploiement avec un dock certifié USB-IF, VESA et DisplayLink qui offre des performances optimales et une compatibilité universelle avec tout PC (Windows, macOS et Ubuntu) ou Chromebook (ChromeOS)
- **FONCTIONNALITÉ UNIVERSELLE USB-C/A** : Se connecte également aux PC USB-A avec un adaptateur USB-C vers A (USB315AC1M); Remarque : la fonction Power Delivery pour charger votre PC n'est pas disponible via USB-A, et seul le double affichage est supporté
- **AVANTAGES POUR LES PROS DE L'IT** : Outils de connectivité inclus pour les pros de l'IT et les

équipes d'assistance IT avec Network MAC Address Pass-Through, WiFi Auto Switching pour améliorer les performances réseau, USB Event Monitoring, et Windows Layout

Matériel

Politique de garantie	3 Years
Prise en charge 4K	Oui
Port(s) à charge rapide	Oui
Écrans pris en charge	3
Type de bus	USB-C
Compatible Lock Slot	Kensington Standard Slot (K-Slot)
Normes de l'industrie	USB Power Delivery Specification Rev. 2.0 USB Battery Charging Specification Rev. 1.2 DisplayPort 1.2 IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0 and 1.1
ID du chipset	DisplayLink - DL-6950 Genesys Logic - GL3523 Texas Instruments - TPS65982 Parade Technologies - PS176

Performance

Vitesse max. de transfert de données	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)
Résolutions numériques max.	1x HDMI (DP Alt Mode) - 4096 x 2160p @24Hz / 3840 x 2160p @30Hz 2x DisplayPort (DisplayLink) - 4096 x 2160p @60Hz / 3840 x 2160p @60Hz 1x 5K DisplayPort using 2 DP video ports - 5120 x 2880 @60Hz

Lower resolutions are also supported. For example, if the max is 3840 x 2160p (4K), it also supports 2560 x 1600p and 2560 x 1440p.

Type et débit	USB 3.0 - 5 Gb/s
Prise en charge UASP	Oui
Réseaux compatibles	10/100/1000 Mbps
MDIX auto	Oui
Prise en charge duplex complet	Oui

Connecteur(s)

Types de connecteur	2 - DisplayPort (20 broches) 1 - HDMI (19 broches) 2 - USB 3.2 Type-C (2 broches, Gen 1, 5Gbps) 1 - USB 3.2 Type-A (9 broches, charge rapide) 3 - USB Type-A (9 broches) USB 3.0 (5 Gbps) 1 - RJ-45 1 - Mini-jack 3,5 mm (4 positions) 2 - Mini-jack 3,5 mm (3 positions) 1 - Fente de verrouillage de sécurité
---------------------	---

Logiciel

Compatibilité système d'exploitation	Windows® 7, 8, 8.1, 10, 11. 11 ARM macOS 10.9 - 10.12, 10.14 - 10.15, 11.0, 12.0, 13.0, 14.0, 15.0, 26.1 Chrome OS™ v55+ Ubuntu 18.04, 20.04, 22.04, 24.04, 24.04
--------------------------------------	---

Notes spéciales / Configuration

Configurations du système et du câblage	USB-C enabled computer with an available USB Type-C port
Remarque	<p>Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 and DP alt mode.</p> <p>4K resolution is supported on all 3 video ports. A 4K-capable DisplayPort display is required to achieve 4Kx2K resolutions</p> <p>If connected to a USB 2.0 host port, or if using a USB 2.0 host connection cable, performance may be limited (USB 3.0 host cable included)</p> <p>USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps</p> <p>5K resolution is supported by connecting the two DisplayPort video ports to a single 5K display. A 5K-capable display is required to achieve 5K (5120 x 2880 60Hz) resolutions</p> <p>The dock connects to the USB-C port on your laptop. The dock can also be connected to the USB-A port on laptops using a USB-C to A cable, sold separately, but only dual display is supported, and Power Delivery to charge your laptop is not available through USB-A</p> <p>DisplayLink docking stations and video adapters support more than one external display on Apple's M1-based Mac. Requires driver installation. Please contact StarTech.com support for a recommendation based on your specific setup.</p>

Alimentation

Source d'alimentation	Adaptateur secteur inclus
Power Delivery	60W
Tension d'entrée	100 - 240 AC
Courant d'entrée	2 A
Tension de sortie	20V DC
Courant de sortie	6 A
Center Tip Polarity	Positif
Type de prise	N

Conditions
environnementales

Température de fonctionnement	0°C to 60°C (32°F to 140°F)
Température de stockage	-20°C to 60°C (-4°F to 140°F)
Humidité	0~95% RH

Caractéristiques
physiques

Couleur	Noir et argent
Type de boîtier	Plastique
Longueur du produit	10.6 in [27 cm]
Largeur du produit	3.2 in [8.2 cm]
Hauteur du produit	1.3 in [3.4 cm]
Poids du produit	13.6 oz [385 g]

Informations
d'emballage

Quantité par paquet	1
Longueur du Paquet	6.5 in [16.5 cm]
Largeur du Colis	11.6 in [29.5 cm]
Hauteur du Paquet	2.9 in [7.3 cm]
Poids brut	3.1 lb [1.4 kg]

Contenu du paquet

Inclus dans le paquet	1 - Station d'Accueil
	1 - 3.3ft (1m) USB-C Cable
	1 - Adaptateur d'alimentation universel (Amérique du Nord/JP, ANZ)
	1 - Manuel d'instruction

1 - Coussinets antidérapants en caoutchouc

Informations de
garantie

Warranty

3 Ans

* L'apparence et les spécifications du produit peuvent être modifiées sans préavis